

GEKA® plus automatic hose reel PA20 and PA20SK

Advantages / benefits: **sturdy, powder-coated steel construction**
automatic roll up of the hose with hose protecting hose guide
gradual adjustment from the distance possible by pulling the hose
fully assembled and ready to use
optimal water throughput for hoses up to 3/4"
 with hose protection and hose stop
 with GEKA® plus 90° angled rotary fitting, brass
 hose guide adjustable in 45° steps
42.9010.9 with 20m GEKA® plus water hose 110 3/4", high-quality, robust
quick couplings and spray nozzle made of brass + 2m supply hose

Material: frame: powder-coated steel; hose guide: white plastic,
 hose stop: black rubber; coil spring, hose protector: stainless steel;
 GEKA® plus angled rotary fitting: brass

Operating pressure: approx. 20 bar

Temperature range: +4 to +60°C (depending on the type of hose)

Dimensions cm: 52,5 x 50,5 x 21

Please note: hose reel is designed for 3/4" hoses with an outside diameter of 24 mm
 screws and wall plugs for wall mounting are not included
rotatable wall mount 90° including connection screws (42.9099.9) available
separately as accessory



wall mount
42.9099.9

	PA20	PA20SK	wall mount
Connection	Male thread	GEKA® plus quick coupling	
Male thread mm	33,25		
Male thread	G1		
Capacity 1/2"-hose approx. m	25	25	
Capacity 5/8"-hose approx. m	25	25	
Capacity 3/4"-hose approx. m	20	20	
Net weight approx. kg	15	24	2
PU units	1	1	1
Item no.	42.9000.9	42.9010.9	42.9099.9

5



sturdy steel construction



GEKA® plus angled rotary fitting with full 3/4" water flow



gradual adjustment



automatic roll-up of the hose



adjustment controllable by pulling the hose at its end



hose protecting hose guide