

GEKA® plus automatic hose reel PA30 and PA30SK

Advantage / benefit: **sturdy, powder-coated steel construction**
automatic roll up of the hose with hose protecting hose guide
gradual adjustment from the distance possible by pulling the hose
fully assembled and ready to use
optimal water throughput for hoses up to 3/4"
rust free inlet pipe and locking mechanism made of stainless steel
with hose protection and hose stop, with GEKA® plus 90° angled rotary fitting, brass
hose guide adjustable in 45° steps, **and therefore ceiling or floor mounting possible**
42.9030.9 with 30 m GEKA® plus water hose 110 3/4", high-quality, robust
quick couplings and spray nozzle made of brass + 2m supply hose

Material: frame: powder-coated steel; hose guide: rolls stainless steel, bracket yellow galvanized steel; hose stop: black rubber; inlet pipe, locking mechanism (crown gear, snap, clip, retaining ring), screws, hose protection clip: stainless steel; GEKA® plus rotary fitting: brass

Operating pressure: approx. 20 bar

Temperature range: +4 to +60°C (depending on the type of hose)

Dimensions LxWxH cm: 61 x 33 x 53

Please note: screws and wall plugs for wall mounting are not included
rotatable wall mount 110° including connection screws (42.9099.9) available separately as accessory



PA30 - 42.9020.9



PA30SK - 42.9030.9

wall mount
42.9098.9*

	PA30 unequipped	PA30SK equipped	wall mount
Connection	Male thread	GEKA® plus Quick coupling	
Male thread mm	33,25		
Male thread	G1		
Capacity 1/2"-hose approx. m	40	40	
Capacity 5/8"-hose approx. m	33	33	
Capacity 3/4"-hose approx. m	30	30	
Capacity 1"-hose approx. m	20	20	
Swivel angle degree	0°	0°	110°
Net weight approx. kg	25,4	34,3	12
PU units	1	1	1
Item no.	42.9020.9	42.9030.9	42.9098.9*

*available from March




sturdy steel construction



GEKA® plus angled rotary fitting with full 3/4" water flow



gradual adjustment



automatic roll-up of the hose



adjustment controllable by pulling the hose at its end



hose protecting hose guide

