

## Professional cleaning gun for hot water, *stainless steel*

Advantage / benefit:	<b>Reinforced safety loop</b> prevents accidental actuation of the operating lever, e.g. when falling down <b>Rubber handle extended on both sides</b> and with a shape that makes it impossible to touch the hot metal parts of the gun or hose fittings <b>Infinitely variable adjustment of jet power</b> <b>Clearly visible water jet direction arrows</b>
Material:	All water-conducting metal parts: stainless steel 1.4401; rubber coating: EPDM
Operating pressure:	<b>Max. 24 bar</b>
Temperature range:	<b>Max. 95 °C; not suitable for steam!</b>
Sealing:	<b>FKM (Fluororubber) according to DIN ISO 1629; Teflon/air insulated</b>
Area of application:	Perfect for cleaning with continuous hot-water applications in industry, business, workshops and food industry
Please note:	Suitable for all GEKA® plus threaded fittings and swivel joints with an external thread of G1/2

### Professional cleaning gun for hot water, stainless steel

Connection	Female thread
Female thread mm	19.17
<b>Female thread</b>	<b>G1/2</b>
Flow volume with 5 bar l/min	25
Weight approx. g	970
PU units	1
Covering box units	20
Catalogue no.	1880
<b>Item no.</b>	<b>23.1880</b>



Female thread connection



Teflon insulation

## GEKA® cleaning gun

Advantage / benefit:	<b>Suitable for drinking water, the used components meet the drinking water ordinance</b> <b>Robust brass/stainless steel combination</b> - guarantees long service life <b>Infinitely variable regulation of jet power, lockable for continuous operation,</b> <b>GEKA® plus push-fit connector, brass, nickel-plated</b>
Material:	Casing: Brass; valve insert: stainless steel; rubber coating on whole gun: EPDM
Operating pressure:	<b>Max. 24 bar</b>
Temperature range:	Max. 50 °C
Sealing:	Seals with KTW approval as per D2 and test certificate DVGW W270
Area of application:	<b>For cleaning of vehicles, sports equipment, garden furniture and small surfaces around the house</b>

### GEKA® cleaning gun

Connection	GEKA® plus push-fit connector
Flow volume with 5 bar l/min	25
Weight approx. g	870
PU units	5
Covering box units	12
Catalogue no.	7850XY
<b>Item no.</b>	<b>46.7002.8</b>

