

# Tank truck couplings TW and accessories

## brass/aluminium

Advantage / benefit:.....forged version, excellent strength and fracture resistance as per EN 14420-6 (previously DIN 28450)

Material:.....brass

Temperature range: .....approx. -10 to +65 °C

Seal: .....NBR

Operating pressure: .....-0.8 to 16 bar

Area of application: .....for shell inclusion

### Type MB blind caps

Nominal width (NW)	50	100
PU units	1	1
Item no.	17.1231	12.1276



### Type VB blind plugs

Advantage / benefit: ..... with hole for chain

Material: ..... brass

Nominal width (NW)	50	80	100
PU units	1	1	1
Item no.	12.1273	12.1274	12.1275



### Clamp collars

Material: ..... aluminium, forged as per DIN 2817

Hose ID mm	25	32	38	50	63	75	100
Hose size	1"	1¼"	1½"	2"	2½"	3"	4"
suitable for hose wall thickness mm	6	6	6.5	8	8	8	8
Clamping range mm	36 - 39	43 - 46	50 - 53	63 - 67	78 - 82	89 - 93	114 - 119
PU units	1	1	1	1	1	1	1
Item no.	83.8337	83.8338	83.8339	83.8340	83.8341	83.8342	83.8343



### Assembly wrench for slotted nuts

Material: ..... steel

Range mm	90-155
PU units	1
Item no.	17.1237



### Chain with S-hook

Material: ..... stainless steel

Area of application: ..... for blind caps and dummy plugs

Approx. length in mm	200
PU units	1
Item no.	17.1238

