

GEKA® plus quick couplings K for drinking water



Change of material:coupling: lead-free brass; seal: blue EPDM

Advantage / benefit:with DVGW type examination certificate (registration number: DW-0310BT0218) for use with hygienically safe drinking water. The blue seal stands for tested hygiene in the drinking water sector – a clear distinguishing feature.

Material:.....coupling: lead-free brass CW508L-DW according to BWGL metal materials in contact with drinking water; seal: EPDM

Claw distance:uniform 40 mm, multiple combinations possible with all other GEKA® versions

Operating pressure:.....**max. 40 bar.** Corresponds to more than double the operating pressure in comparison with the common claw couplings according to GEKA® system


Vacuum resistance:.....up to 10 m water column (WS)

Temperature range:.....-10 °C to +85 °C

Seal:.....as standard with GEKA® plus shaped seal 300K, for drinking water, with KTW BWGL, DIN EN 16421

Area of application:.....For the temporary transport of drinking water in accordance with VP550, in the food industry, in drinking water installations in gardens and outdoor areas, e.g. outdoor kitchens, and at public events such as fairs, outdoor events and similar occasions; also suitable for use with chlorinated water, e.g. in swimming pools or chlorinated drinking water..

1



GEKA® plus hose pieces K

Grommet with striking and hose protecting ribbed profile guarantees fixed hose fit. For clamps and ferrules

Hose ID mm	10	13	16	19	25	32	38
Hose size	3/8"	1/2"	5/8"	3/4"	1"	1¼"	1½"
PU units	10	10	10	10	10	10	5
Covering box units	160	150	130	120	100	70	60
Item no.	02.0200	02.0201	02.0202	02.0203	02.0204	02.0206	02.0207



GEKA® plus threaded fittings K with female thread

EPDM flat seal ring on the threaded side. DIN EN 16421 + KTW BWGL, blue

Female thread in mm	15.39	19.17	24.66	30.93	39.59	45.48
Female thread	G3/8	G1/2	G3/4	G1	G1¼	G1½
PU units	10	10	10	10	10	10
Covering box units	180	160	160	140	100	120
Item no.	02.1209	02.1210	02.1211	02.1213	02.1214	02.1216



GEKA® plus threaded fittings K with male thread

Male thread in mm	16.66	20.95	26.44	33.25	41.91	47.80
Male thread	G3/8	G1/2	G3/4	G1	G1¼	G1½
PU units	10	10	10	10	10	10
Covering box units	180	180	170	160	130	110
Item no.	02.2209	02.2210	02.2211	02.2213	02.2214	02.2216



GEKA® plus dummy coupling K

With bore for chain fastening

PU units	10
Covering box units	180
Item no.	02.3218

Special note: Made from lead-free brass CW508L-DW, the quick coupling already meets the requirements of the assessment basis for metallic materials in contact with drinking water, according to which only products made of lead-free brass may be newly installed in water supply systems from 11 January 2028.

The new blue EPDM seal already meets the requirements of the KTW assessment basis, which will become legally binding on 1 July 2026.

Brass is not suitable for all cleaning agents. In special cases, GEKA® plus couplings made of stainless steel must be used.